

ELECTROCHEMISTRY

ELECTRODE POTENTIAL

For any electrode → oxidation potential = – Reduction potential

$$E_{\text{cell}} = \text{R.P. of cathode} - \text{R.P. of anode}$$

$$E_{\text{cell}} = \text{R.P. of cathode} + \text{O.P. of anode}$$

E_{cell} is always a +ve quantity & Anode will be electrode of low R.P

$$E_{\text{cell}}^{\circ} = \text{SRP of cathode} - \text{SRP of anode.}$$

- Greater the SRP value greater will be oxidising power.

GIBBS FREE ENERGY CHANGE :

$$\Delta G = -nFE_{\text{cell}}$$

$$\Delta G^{\circ} = -nFE_{\text{cell}}^{\circ}$$

NERNST EQUATION : (Effect of concentration and temp on emf of cell)

$$\Delta G = \Delta G^{\circ} + RT \ln Q \quad (\text{where } Q \text{ is reaction quotient})$$

$$\Delta G^{\circ} = -RT \ln K_{\text{eq}}$$

$$E_{\text{cell}} = E_{\text{cell}}^{\circ} - \frac{RT}{nF} \ln Q$$

$$E_{\text{cell}} = E_{\text{cell}}^{\circ} - \frac{2.303RT}{nF} \log Q$$

$$E_{\text{cell}} = E_{\text{cell}}^{\circ} - \frac{0.0591}{n} \log Q \quad [\text{At } 298 \text{ K}]$$

At chemical equilibrium

$$\Delta G = 0 \quad ; \quad E_{\text{cell}} = 0.$$

- $\log K_{\text{eq}} = \frac{nE_{\text{cell}}^{\circ}}{0.0591}$

$$E_{\text{cell}}^{\circ} = \frac{0.0591}{n} \log K_{\text{eq}}$$

For an electrode $M(s)/M^{n+}$.

$$E_{M^{n+}/M} = E_{M^{n+}/M}^{\circ} - \frac{2.303RT}{nF} \log \frac{1}{[M^{n+}]}$$

CONCENTRATION CELL :

A cell in which both the electrodes are made up of same material.

For all concentration cell $E^{\circ}_{\text{cell}} = 0$.

(a) Electrolyte Concentration Cell :

eg. $\text{Zn(s)} / \text{Zn}^{2+} (c_1) \parallel \text{Zn}^{2+} (c_2) / \text{Zn(s)}$

$$E = \frac{0.0591}{2} \log \frac{C_2}{C_1}$$

(b) Electrode Concentration Cell :

eg. $\text{Pt, H}_2(P_1 \text{ atm}) / \text{H}^+ (1\text{M}) \parallel \text{H}_2 (P_2 \text{ atm}) / \text{Pt}$

$$E = \frac{0.0591}{2} \log \left(\frac{P_1}{P_2} \right)$$

DIFFERENT TYPES OF ELECTRODES :

1. Metal-Metal ion Electrode $\text{M(s)}/\text{M}^{n+}$. $\text{M}^{n+} + n\text{e}^- \longrightarrow \text{M(s)}$

$$E = E^{\circ} + \frac{0.0591}{n} \log[\text{M}^{n+}]$$

2. Gas-ion Electrode $\text{Pt}/\text{H}_2(P_{\text{atm}})/\text{H}^+ (X\text{M})$
as a reduction electrode



$$E = E^{\circ} - 0.0591 \log \frac{P_{\text{H}_2}^{\frac{1}{2}}}{[\text{H}^+]}$$

3. Oxidation-reduction Electrode $\text{Pt} / \text{Fe}^{2+}, \text{Fe}^{3+}$
as a reduction electrode $\text{Fe}^{3+} + \text{e}^- \longrightarrow \text{Fe}^{2+}$

$$E = E^{\circ} - 0.0591 \log \frac{[\text{Fe}^{2+}]}{[\text{Fe}^{3+}]}$$

4. Metal-Metal insoluble salt Electrode eg. $\text{Ag}/\text{AgCl}, \text{Cl}^-$
as a reduction electrode $\text{AgCl(s)} + \text{e}^- \longrightarrow \text{Ag(s)} + \text{Cl}^-$

$$E_{\text{Cl}^- / \text{AgCl} / \text{Ag}} = E^{\circ}_{\text{Cl}^- / \text{AgCl} / \text{Ag}} - 0.0591 \log [\text{Cl}^-].$$

(a) $K^+, Ca^{+2}, Na^+, Mg^{+2}, Al^{+3}, Zn^{+2}, Fe^{+2}, H^+, Cu^{+2}, Ag^+, Au^{+3}$.

$\xrightarrow{\hspace{15em}}$
 Increasing order of deposition.

(b) Similarly the anion which is stronger reducing agent (low value of SRP) is liberated first at the anode.

$\xrightarrow{SO_4^{2-}, NO_3^-, OH^-, Cl^-, Br^-, I^-}$
 Increasing order of deposition

FARADAY'S LAW OF ELECTROLYSIS :

First Law :

$$w = zq$$

$$w = Z it \quad Z = \text{Electrochemical equivalent of substance}$$

Second Law :

$$W \propto E$$

$$\frac{W}{E} = \text{constant} \quad \frac{W_1}{E_1} = \frac{W_2}{E_2} = \dots\dots\dots$$

$$\frac{W}{E} = \frac{i \times t \times \text{current efficiency factor}}{96500}$$

$$\text{Current efficiency} = \frac{\text{actual mass deposited/produced}}{\text{Theoretical mass deposited/produced}} \times 100$$

CONDITION FOR SIMULTANEOUS DEPOSITION OF Cu & Fe AT CATHODE

$$E^{\circ}_{Cu^{2+}/Cu} - \frac{0.0591}{2} \log \frac{1}{Cu^{2+}} = E^{\circ}_{Fe^{2+}/Fe} - \frac{0.0591}{2} \log \frac{1}{Fe^{2+}}$$

Condition for the simultaneous deposition of Cu & Fe on cathode.

CONDUCTANCE :

☞ Conductance = $\frac{1}{\text{Resistance}}$

☞ Specific conductance or conductivity :

(Reciprocal of specific resistance) $K = \frac{1}{\rho}$

K = specific conductance

☞ Equivalent conductance :

$$\lambda_E = \frac{K \times 1000}{\text{Normality}} \quad \text{unit : } -\text{ohm}^{-1} \text{ cm}^2 \text{ eq}^{-1}$$

☞ Molar conductance :

$$\lambda_m = \frac{K \times 1000}{\text{Molarity}} \quad \text{unit : } -\text{ohm}^{-1} \text{ cm}^2 \text{ mole}^{-1}$$

$$\text{specific conductance} = \text{conductance} \times \frac{l}{a}$$

KOHLRAUSCH'S LAW :

Variation of $\lambda_{\text{eq}} / \lambda_M$ of a solution with concentration :

(i) **Strong electrolyte**

$$\lambda_M^c = \lambda_M^\infty - b\sqrt{c}$$

(ii) **Weak electrolytes :** $\lambda_\infty = n_+ \lambda_+^\infty + n_- \lambda_-^\infty$

where λ is the molar conductivity

n_+ = No of cations obtained after dissociation per formula unit

n_- = No of anions obtained after dissociation per formula unit

APPLICATION OF KOHLRAUSCH LAW :

1. **Calculation of λ_M^0 of weak electrolytes :**

$$\lambda_{M(\text{CH}_3\text{COOH})}^0 = \lambda_{M(\text{CH}_3\text{COONa})}^0 + \lambda_{M(\text{HCl})}^0 - \lambda_{M(\text{NaCl})}^0$$

2. To calculate degree of dissociation of a weak electrolyte

$$\alpha = \frac{\lambda_m^c}{\lambda_m^0} \quad ; \quad K_{\text{eq}} = \frac{c\alpha^2}{(1-\alpha)}$$

3. Solubility (S) of sparingly soluble salt & their K_{sp}

$$\lambda_M^c = \lambda_M^\infty = \kappa \times \frac{1000}{\text{solubility}}$$

$$K_{\text{sp}} = S^2.$$

Transport Number :

$$t_c = \left[\frac{\mu_c}{\mu_c + \mu_a} \right], \quad t_a = \left[\frac{\mu_a}{\mu_a + \mu_c} \right].$$

Where t_c = Transport Number of cation & t_a = Transport Number of anion