

ELECTROMAGNETIC INDUCTION

1. **Magnetic flux** is mathematically defined as $\phi = \int \vec{B} \cdot d\vec{s}$
2. **Faraday's laws of electromagnetic induction**

$$E = - \frac{d\phi}{dt}$$

3. **Lenz's Law** (conservation of energy principle)
According to this law, emf will be induced in such a way that it will oppose the cause which has produced it.
Motional emf

4. **Induced emf due to rotation**

Emf induced in a conducting rod of length l rotating with angular speed ω about its one end, in a uniform perpendicular magnetic field B is $\frac{1}{2} B \omega l^2$.

- 4.1. **EMF Induced in a rotating disc :**

Emf between the centre and the edge of disc of radius r rotating in a

magnetic field $B = \frac{B\omega r^2}{2}$

5. **Fixed loop in a varying magnetic field**

If magnetic field changes with the rate $\frac{dB}{dt}$, electric field is generated

whose average tangential value along a circle is given by $E = \frac{r}{2} \frac{dB}{dt}$

This electric field is non conservative in nature. The lines of force associated with this electric field are closed curves.

6. Self induction


$$\varepsilon = -\frac{\Delta(N\phi)}{\Delta t} = -\frac{\Delta(LI)}{\Delta t} = -\frac{L\Delta I}{\Delta t}$$

The instantaneous emf is given as $\varepsilon = -\frac{d(N\phi)}{dt} = -\frac{d(LI)}{dt} = -\frac{LdI}{dt}$

Self inductance of solenoid = $\mu_0 n^2 \pi r^2 l$.

6.1 Inductor

It is represent by
electrical equivalence of loop



Energy stored in an inductor = $\frac{1}{2} LI^2$


7. Growth Of Current in Series R–L Circuit

If a circuit consists of a cell, an inductor L and a resistor R and a switch S ,connected in series and the switch is closed at $t = 0$, the current in the

circuit I will increase as $I = \frac{\varepsilon}{R} (1 - e^{-\frac{Rt}{L}})$

The quantity L/R is called time constant of the circuit and is denoted by τ .
The variation of current with time is as shown.

1. Final current in the circuit = $\frac{\varepsilon}{R}$, which is independent of L.



2. After one time constant , current in the circuit =63% of the final current.

3. More time constant in the circuit implies slower rate of change of current.

8 Decay of current in the circuit containing resistor and inductor:

Let the initial current in a circuit containing inductor and resistor be I_0 .

Current at a time t is given as $I = I_0 e^{-\frac{Rt}{L}}$


Current after one time constant : $I = I_0 e^{-1} = 0.37\%$ of initial current.

9. Mutual inductance is induction of EMF in a coil (secondary) due to change in current in another coil (primary). If current in primary coil is I , total flux in secondary is proportional to I , i.e. $N \phi$ (in secondary) $\propto I$.

or $N \phi$ (in secondary) = $M I$.

The emf generated around the secondary due to the current flowing around the primary is directly proportional to the rate at which that current changes.

10. Equivalent self inductance :



1. Series combination :

$L = L_1 + L_2$ (neglecting mutual inductance)

$L = L_1 + L_2 + 2M$ (if coils are mutually coupled and they have winding in same direction)

$L = L_1 + L_2 - 2M$ (if coils are mutually coupled and they have winding in opposite direction)

2. Parallel Combination :


$\frac{1}{L} = \frac{1}{L_1} + \frac{1}{L_2}$ (neglecting mutual inductance)

For two coils which are mutually coupled it has been found that $M \leq \sqrt{L_1 L_2}$

or $M = k \sqrt{L_1 L_2}$ where k is called coupling constant and its value is less than or equal to 1.

$\frac{E_s}{E_p} = \frac{N_s}{N_p} = \frac{I_p}{I_s}$, where denotations have their usual meanings.

$\Rightarrow \frac{N_s > N_p}{E_s > E_p} \rightarrow$
for step up transformer.



11. LC Oscillations

$\omega^2 = \frac{1}{LC}$